NSN 5910-00-333-9776

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-333-9776 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Diameter: |
| 0.462 inches |
| Body Length: |
| 1.188 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 0.470 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 70.0 degrees celsius |
| Detween -55.0 degrees ceisius and 70.0 degrees ceisius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead |

No

Demilitarization:

NSN 5910-00-333-9776

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0