NSN 5910-00-340-1634

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-340-1634

Body Style:			
W/thd mtg bushing, terminals on opposite ends			
Reliability Indicator:			
Not established			
Width Across Flats:			

Terminal Length: 38.1 millimeters

10.0 millimeters

Body Length:

_--u, _-...g....

20.0 millimeters

Terminal Diameter:

0.6 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Screw Thread Series Designator:

Iso m

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Mounting hardware

Capacitance Value Per Section:

1500.000 picofarads single section

Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-70.0 to 30.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -30.00 degrees celsius and 85.0 degrees celsius

Thread Size:

7.0 millimeters

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-0.00 to 100.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

2.5000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-340-1634

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



She	lf I	Life	е:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0