## NSN 5910-00-340-1678



Electrolytic Fixed Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-00-340-1678

Body Style:

W/o mtg facilities, axial terminals

Mil-std-1276 Wire Lead Type Designator:

C

Reliability Indicator:

Not established

Terminal Length:

50.000 millimeters

Body Diameter:

13.000 millimeters

27.000 millimeters

Terminal Diameter:

0.025 inches

**Body Length:** 

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

365.0

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

10.000 microfarads single section

**Nonderated Operating Temp:** 

Between -20.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

15.1000

Dc Leakage At Reference Temp:

15.000 microamperes

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-340-1678

Electrolytic Fixed Capacitor - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0