NSN 5910-00-350-1221

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-350-1221

| Body | Stv | ٠ ما |
|-------------|------|------|
| DOUV | OLV. | ıe. |

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

Between 4.500 inches and 4.626 inches

Body Width:

Between 3.687 inches and 3.813 inches

Body Height:

Between 4.312 inches and 4.438 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 1.812 inches and 2.063 inches

Terminal Diameter:

0.164 inches

Terminal Height From Body:

Between 1.125 inches and 1.375 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

12.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

2500.0 dc single section

Tolerance Range Per Section:

-20.00 to 20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

Power Factor At Reference Tempurature In Percent:

1.000

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5910-00-350-1221

Paper Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0