## NSN 5910-00-350-1868

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5910-00-350-1666
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.860 inches
Body Width:
0.700 inches
Body Height:
0.300 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.390 inches and 0.410 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.390 microfarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-20.0/+0.0 with rated voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
2.5000
Terminal Surface Treatment:
Solder
Test Data Document:
18876-mis13295 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:

N/a

**Unit Of Measure:** 

Shelf Life:

2 uninsulated wire lead

## NSN 5910-00-350-1868

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0