## NSN 5910-00-350-7716

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-350-7716

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 1.000 inches and 1.500 inches

**Body Length:** 

Between 0.470 inches and 0.530 inches

**Body Width:** 

Between 0.250 inches and 0.310 inches

**Body Height:** 

Between 0.110 inches and 0.140 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.395 inches and 0.405 inches

**Terminal Diameter:** 

Between 0.019 inches and 0.021 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

0.0012 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-50.0/+50.0 single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

1000000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.150

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-350-7716

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:
N/a	
11:40	4 14-

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0