NSN 5910-00-350-7716

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-350-7716

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 1.000 inches and 1.500 inches

Body Length:

Between 0.470 inches and 0.530 inches

Body Width:

Between 0.250 inches and 0.310 inches

Body Height:

Between 0.110 inches and 0.140 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.395 inches and 0.405 inches

Terminal Diameter:

Between 0.019 inches and 0.021 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

0.0012 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

1000000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.150

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-350-7716

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:
N/a	
11:40	4 14-

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0