Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-356-1676

#### **Body Style:**

W/o mtg facilities, axial terminals

#### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.219 inches

#### **Body Length:**

0.515 inches

## **Terminal Diameter:**

0.025 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

## Impedance At Minimum Operating Tempurature In Ohms:

220.0

#### **Electrical Polarization:**

Polarized

## **Features Provided:**

Hermetically sealed case

#### Capacitance Value Per Section:

10.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

2.0 microamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

## **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Metal

# **Capacitive Electrode Material:**

Tantalum

## Power Factor At Reference Tempurature In Percent:

4.6000

## Dc Leakage At Reference Temp:

1.000 microamperes

# **Terminal Surface Treatment:**

Solder

Electrolytic Fixed Capacitor - Page 2 of 2



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0