

View Online at <https://aerobasegroup.com/nsn/5910-00-357-9721>

Body Style:

W/o mtg facilities, axial terminals

Mil-std-1276 Wire Lead Type Designator:

C

Reliability Indicator:

Not established

Terminal Length:

30.000 millimeters

Body Diameter:

11.400 millimeters

Body Length:

30.000 millimeters

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

20000.000 picofarads single section

Nonderated Operating Temp:

Between -10.0 degrees celsius and 70.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

125.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

0.2 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

0.0500

Quality Factor At Reference Temp:

20000.0000

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0