Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-361-9582

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

#### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

#### **Body Length:**

0.500 inches

#### **Body Width:**

0.280 inches

### **Body Height:**

#### 0.125 inches

# Center To Center Distance Between Terminals Parallel To Length:

0.400 inches

#### **Terminal Diameter:**

0.020 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

# Capacitance Value Per Section:

10000.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0