Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-370-2326

## **Body Style:**

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

0.750 inches

# Body Length:

1.312 inches

#### **Body Width:**

0.828 inches

**Body Height:** 

#### 2.750 inches

Center To Center Distance Between Terminals Parallel To Length:

0.625 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

## Capacitance Value Per Section:

0.750 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

330.0 ac-rms single section

### **Tolerance Range Per Section:**

-6.00 to 6.00 percent single section

## **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

### **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# NSN 5910-00-370-2326

Paper Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

