NSN 5910-00-390-9736

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-390-9/36
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.500 inches
Body Width:
0.375 inches
Body Height:
0.195 inches
Center To Center Distance Between Terminals Parallel To Length:
0.400 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
1000.0 megohms
Capacitance Value Per Section:
22000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.3000
Terminal Surface Treatment:
Solder

Dielectric Material: Plastic polyparaxylene

NSN 5910-00-390-9736

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Γerminal Type And Qι	uantity:
----------------------	----------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0