Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-396-2782

### **Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:** 

Not established

## **Terminal Length:**

0.750 inches

#### **Body Length:**

1.812 inches

#### **Body Width:**

1.000 inches

#### **Body Height:**

#### 1.000 inches

#### Center To Center Distance Between Terminals Parallel To Length:

1.062 inches

#### **Unthreaded Mounting Hole Diameter:**

### 0.188 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.125 inches

### Schematic Diagram Designator:

Delta connected

### Mounting Facility Type And Quantity:

2 unthreaded mounting holes

#### Section Quantity:

3

# Features Provided:

Hermetically sealed case

## Capacitance Value Per Section:

36000.000 picofarads all sections

# Nonderated Operating Temp:

Between -21.0 degrees celsius and 75.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

150.0 ac-rms all sections

# **Tolerance Range Per Section:**

-0.00 to 10.00 percent single section

## Case Material:

Metal

# **Terminal Surface Treatment:**

Solder

# **Dielectric Material:**

Plastic

# Terminal Type And Quantity:

3 tab, solder lug

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0