NSN 5910-00-401-6381

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-401-6381

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.420 inches
Body Width:
0.170 inches
Body Height:
0.290 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
47000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-2.00/+2.00 percent single section
Case Material:
Plastic
T Idollo
Insulation Resistance At Reference Temp:
Insulation Resistance At Reference Temp:
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment:
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

Fiig:

A010b0