Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-401-6504

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.250 inches

**Body Length:** 

0.500 inches

#### **Body Width:**

0.375 inches

**Body Height:** 

#### 0.195 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.395 inches and 0.405 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

## Capacitance Value Per Section:

22000.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

## **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

1000000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.1500

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

# Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0