NSN 5910-00-401-7752

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-401-7752

Body Style: W/mtg tabs/flanges, terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 1.812 inches **Body Width:** 0.875 inches **Body Height:** 1.250 inches **Unthreaded Mounting Hole Diameter:** 0.188 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.125 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Type And Quantity:** 2 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Dissipation Factor At Reference Tempurature In Percent: Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-18312 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:**

2 tab, solder lug

Specification Data:

81349-mil-c-18312/5 government specification

Shelf Life:

N/a

NSN 5910-00-401-7752

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0