NSN 5910-00-402-1486

Body Style:

0.500 microamperes

Solder

Terminal Surface Treatment:

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-402-1486

W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.285 inches
Body Width:
0.225 inches
Body Height:
0.170 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.195 inches and 0.205 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Polarized
Capacitance Value Per Section:
0.470 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
Dc Leakage At Maximum Operating Temp: 5.0 milliamperes
5.0 milliamperes
5.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section:
5.0 milliamperesNonderated Continuous Voltage Rating And Type Per Section:35.0 dc single section
5.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section:
5.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
5.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
5.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic
5.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material:
5.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum

NSN 5910-00-402-1486

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type A	and Quantity	/:
-----------------	--------------	-----------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0