NSN 5910-00-402-1675

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-402-1675

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
2.000 inches
Body Diameter:
0.437 inches
Body Length:
1.562 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
37.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
270.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
5.0 dc single section
Tolerance Range Per Section:
-10.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
20.0000
Dc Leakage At Reference Temp:
2.000 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
81349-milc62/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
evolutes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

2 uninsulated wire lead

Terminal Type And Quantity:

NSN 5910-00-402-1675

Electrolytic Fixed Capacitor - Page 2 of 2



		fe:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0