## NSN 5910-00-402-1910

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-402-1910 **Body Style:** Plate-meshing **Overall Length:** Between 0.703 inches and 0.765 inches **Terminal Length:** 0.156 inches **Overall Height:** 0.512 inches **Overall Width:** 0.433 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 45.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -15.0/+15.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.500 inches **Quality Factor At 25 Deg Celsius:** 1500.0 **Fragility Factor:** Moderately rugged **Terminal Width:** 0.047 inches **Inclosure Type:** Uninclosed **Plate Quantity:** 16 **Tuning Characteristic:** Straight line capacity single section **Split-stator Rotary Plate Type:** Butterfly **Adjustment Device Torque:** Between 2.500 inch-ounces and 10.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms Plate Air Gap: 0.010 inches **Mounting Facility Type And Quantity:** 3 terminal **Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

**Capacitance Range In Picofarads:** 

+1.9/+8.5 single section

## NSN 5910-00-402-1910

Air Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type:
650.0 ac peak single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Material:
Steatite base
Precious Material And Location:
Metal surfaces silver
Precious Material:
Silver
Terminal Type And Quantity:
3 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0