NSN 5910-00-402-9081

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-402-9081 **Body Style:** Piston **Overall Length:** 1.453 inches **Body Length:** 1.328 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -100.0/+100.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.281 inches Center To Center Distance Between Terminals Parallel To Diameter: 0.234 inches **Quality Factor At 25 Deg Celsius:** 700.0 **Inclosure Type: Encased Adjustment Device Rotation:** 1.5 turns clockwise **Mounting Facility Type And Quantity:** 4 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +0.8/+23.0 single section **Nonderated Voltage Rating And Type:** 1250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Capacitance Drift In Picofarads: 0.04 single section **Test Data Document:** 81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 4 wire lead Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5910-00-402-9081

Glass Dielectric Variable Capacitor - Page 2 of 2



Fiig:

A096a0