## NSN 5910-00-403-2438

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-403-2438 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.685 inches **Body Width:** 0.670 inches **Body Height:** 0.195 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.570 inches and 0.630 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 100.0 megohm-microfarads **Capacitance Value Per Section:** 0.270 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 5000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5910-00-403-2438

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0