NSN 5910-00-403-4632 Ceramic Dielectric Variable Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-403-4632
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
-650.0 single section
Quality Factor At 25 Deg Celsius:
500.0
Inclosure Type:
Encased
Adjustment Device Torque:
Between 1.000 inch-ounces and 6.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
10.0 gigohms
Mounting Facility Type And Quantity:
2 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Capacitance Range In Picofarads:
+9.0 to 35.0 single section
Nonderated Voltage Rating And Type:
200.0 dc continuous single section
Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius:
+1.50 to 7.00 and -8.50/-2.50 single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.50 single section
Terminal Type And Quantity:
2 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A096a0