## NSN 5910-00-404-1929

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-404-1929 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Length:** 0.703 inches **Body Width:** 0.312 inches **Body Height:** 0.203 inches **Center To Center Distance Between Terminals Parallel To Length:** Between 0.345 inches and 0.405 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 25.0 megohm-microfarads **Capacitance Value Per Section:** 15000.000 picofarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 25000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Test Data Document:** 19315-qb99503 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5910-00-404-1929

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0