NSN 5910-00-406-9737

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-406-9737 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 2.000 inches **Body Diameter:** 0.296 inches **Body Length:** 1.000 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Etched foil **Impedance At Minimum Operating Tempurature In Ohms:** 83.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 22.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 9.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Equivalent Series Resistance At Reference Tempurature In Ohms:** 135.00 Dc Leakage At Reference Temp: 3.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:**

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-406-9737

Electrolytic Fixed Capacitor - Page 2 of 2



| She | lf I | Life: |
|-----|------|-------|
| | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0