

View Online at https://aerobasegroup.com/nsn/5910-00-407-1515

Body Style:	
Piston	
Overall Length:	
1.515 inches	
Body Length:	
1.359 inches	
Overall Diameter:	
0.312 inches	
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius	
+0.0/+50.0 single section	
Center To Center Distance Between Terminals Parallel To Length:	
1.016 inches	
Center To Center Distance Between Terminals Parallel To Diameter:	
Between 0.234 inches and 0.281 inches	
Quality Factor At 25 Deg Celsius:	
1500.0	
Inclosure Type:	
Encased	
Adjustment Device Torque:	
Between 1.000 inch-ounces and 10.000 inch-ounces	
Insulation Dc Resistance At 25 Deg Celsius:	
1000.0 gigohms	
Mounting Facility Type And Quantity:	
2 terminal	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 150.0 degrees celsius	
Capacitance Range In Picofarads:	
+0.6/+9.5 single section	
Nonderated Voltage Rating And Type:	
1250.0 dc continuous single section	
Adjustment Device Drive Type And Quantity:	
1 slotted screw	
Capacitance Drift In Picofarads:	
0.01 single section	
Test Data Document:	
81349-mil-c-14409 specification (includes engineering type bulletins, brochu	res. etc that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trad-	
environmental and performance requirements and test conditions that are sho	
Terminal Type And Quantity:	, , , , , , , , , , , , , , , , , , ,
2 wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	

---



Demilitarization:

No

Fiig:

A096a0