## NSN 5910-00-410-1262

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-410-1262

**Body Style:** Piston **Overall Length:** 1.000 inches **Shaft Length:** 0.125 inches single shaft **Body Length:** 0.875 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section Center To Center Distance Between Terminals Parallel To Length: 0.703 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.281 inches **Quality Factor At 25 Deg Celsius:** 900.0 **Inclosure Type: Encased Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100.0 gigohms **Mounting Facility Type And Quantity:** 4 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Shaft Type:** Round, slotted single shaft Capacitance Range In Picofarads: +0.8/+11.0 single section **Nonderated Voltage Rating And Type:** 1250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 shaft Capacitance Drift In Picofarads: 0.02 single section **Test Data Document:** 81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

4 wire lead

**Terminal Type And Quantity:** 

## NSN 5910-00-410-1262

Glass Dielectric Variable Capacitor - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0