NSN 5910-00-410-1880

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-410-1880 **Body Style:** Piston **Overall Length:** 0.812 inches **Body Length:** 0.656 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.500 inches Center To Center Distance Between Terminals Parallel To Diameter: Between 0.234 inches and 0.281 inches **Quality Factor At 25 Deg Celsius:** 1000.0 **Inclosure Type:** Encased **Insulation Dc Resistance At Max Operating Temp:** 100.0 gigohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +0.8/+5.5 single section **Nonderated Voltage Rating And Type:** 750.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Capacitance Drift In Picofarads: 0.02 single section **Test Data Document:** 81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5910-00-410-1880

Glass Dielectric Variable Capacitor - Page 2 of 2



Fiig:

A096a0