NSN 5910-00-410-2444

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-410-2444

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Diameter:
0.453 inches
Body Length:
1.250 inches
Terminal Diameter:
Between 0.025 inches and 0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Wasp class Ihd, forrestal class cv, kidd class ddg, general purpose electronic test equipment, virginia class cg (41), oliver perry class ffg
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
2.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 105.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.3000
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead

N/a

Shelf Life:

NSN 5910-00-410-2444

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A010b0