## NSN 5910-00-410-3890

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-410-3890

**Body Style:** 

Piston

**Overall Length:** 

Between 1.251 inches and 1.375 inches

**Terminal Length:** 

0.500 inches

**Body Length:** 

Between 1.126 inches and 1.250 inches

**Overall Diameter:** 

0.312 inches

Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

**Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** 

-150.0/+150.0 single section

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 1.079 inches and 1.203 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.234 inches

**Terminal Diameter:** 

0.029 inches

**Quality Factor At 25 Deg Celsius:** 

350.0

**Fragility Factor:** 

Moderately rugged

**Inclosure Type:** 

Encased

**Adjustment Device Torque:** 

Between 1.000 inch-ounces and 10.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Insulation Dc Resistance At Max Operating Temp:

100000.0 megohms

**Mounting Facility Type And Quantity:** 

4 terminal

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+1.0/+52.0 single section

**Nonderated Voltage Rating And Type:** 

1000.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:** 

1 slotted screw

## NSN 5910-00-410-3890

Glass Dielectric Variable Capacitor - Page 2 of 2



Material:
Glass inclosure
Terminal Type And Quantity
4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A096a0