## NSN 5910-00-410-3942

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-410-3942

**Body Style:** 

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.500 inches

**Body Length:** 

1.094 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**Mounting Facility Screw Thread Series Designator:** 

Unf

**Mounting Facility Type And Quantity:** 

1 threaded bushing

**Features Provided:** 

Mounting hardware and hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

5000.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.470 microfarads single section

**Nonderated Operating Temp:** 

Between -65.0 degrees celsius and 85.0 degrees celsius

**Thread Size:** 

0.312 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.6000

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-19978+1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-410-3942

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0