## NSN 5910-00-412-0781

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-412-0781

| Body Style:  |
|--|
| W/mtg tabs/flanges, terminals on opposite surfaces                           |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 0.750 inches   |
| Body Length:   |
| 2.000 inches   |
| Body Width:  |
| 2.000 inches   |
| Body Height:   |
| 1.000 inches   |
| Center To Center Distance Between Terminals Parallel To Length:              |
| 1.062 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.188 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.375 inches   |
| Schematic Diagram Designator:  |
| One terminal common to each section  |
| Internal Electrical Connection Type:   |
| Extended foil  |
| Mounting Facility Type And Quantity:   |
| 2 unthreaded mounting holes  |
| Section Quantity:  |
| 3  |
| Features Provided:   |
| Hermetically sealed case   |
| Capacitance Value Per Section:   |
| 0.500 microfarads all sections   |
| Nonderated Operating Temp:   |
| Between -60.0 degrees celsius and 120.0 degrees celsius                      |
| Nonderated Continuous Voltage Rating And Type Per Section:                   |
| 600.0 dc all sections  |
| Tolerance Range Per Section:   |
| +0.00 to 100.00 percent all sections   |
| Case Material:   |
| Metal  |
| Terminal Surface Treatment:  |
| Solder   |
| Terminal Type And Quantity:  |

4 tab, solder lug

## NSN 5910-00-412-0781

Paper Dielectric Fixed Capacitor - Page 2 of 2



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0