NSN 5910-00-414-7881

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-414-7881

Body Style:

W/thd mtg hol (s)/stud(s), terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

1.593 inches

Body Width:

1.000 inches

Body Height:

3.125 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Etched foil

Impedance At Minimum Operating Tempurature In Ohms:

2.5

Electrical Polarization:

Polarized

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.500 inches

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

2 threaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

3000.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.190 inches

Dc Leakage At Maximum Operating Temp:

138.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Electrolytic Fixed Capacitor - Page 2 of 2



Dissipation Factor At Reference Tempurature In Percent:

12.0000

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.15

Dc Leakage At Reference Temp:

22.500 microamperes

Terminal Surface Treatment:

Solder

Special Features:

Mtg holes located opposite terminal end

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0