Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-416-9697

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.625 inches

**Body Length:** 

0.500 inches

#### **Body Width:**

0.471 inches

**Body Height:** 

#### 0.234 inches

## Center To Center Distance Between Terminals Parallel To Length:

Between 0.395 inches and 0.405 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

1000.0 megohm-microfarads

## **Capacitance Value Per Section:**

10000.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

## **Dissipation Factor At Reference Tempurature In Percent:**

0.5000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-416-9697

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

