## NSN 5910-00-419-2876

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-419-2876

| Body Style:  |
|--|
| W/o mtg facilities, terminals on opposite surfaces         |
| Reliability Indicator:                                     |
| Not established  |
| Terminal Length:   |
| 2.000 inches   |
| Body Length:   |
| 0.680 inches   |
| Body Width:  |
| 0.170 inches   |
| Body Height:   |
| 0.300 inches   |
| Terminal Diameter:   |
| 0.020 inches   |
| Schematic Diagram Designator:                              |
| No common or grounded electrode (s)                        |
| Insulation Resistance At Maximum Operating Temp:           |
| 200.0 megohms  |
| Capacitance Value Per Section:                             |
| 0.330 microfarads single section                           |
| Nonderated Operating Temp:                                 |
| Between -55.0 degrees celsius and 85.0 degrees celsius     |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section                                    |
| Tolerance Range Per Section:                               |
| -5.00/+5.00 percent single section                         |
| Case Material:   |
| Plastic  |
| Insulation Resistance At Reference Temp:                   |
| 100000.0 megohms   |
| Dissipation Factor At Reference Tempurature In Percent:    |
| 1.0000   |
| Terminal Surface Treatment:                                |
| Solder   |
| Terminal Type And Quantity:                                |
| 2 uninsulated wire lead                                    |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| _  |
| Demilitarization:  |

No

## NSN 5910-00-419-2876

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0