

View Online at <https://aerobasegroup.com/nsn/5910-00-419-2877>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Not established

**Body Diameter:**

2.080 inches

**Body Length:**

4.000 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Electrical Polarization:**

Polarized

**End Application:**

Kidd class ddg, emory s. Land class as, forrestal class cv, austin ship class lpd-4 amphibious transport docks, nimitz class cvn, oliver perry class ffg, wasp class lhd, tarawa class lha, supply class aoe

**Capacitance Value Per Section:**

5600.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-10.00/+100.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

45.0000

**Dc Leakage At Reference Temp:**

790.000 microamperes

**Case Insulation Material:**

Plastic

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0