Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-419-7521

### **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

## **Terminal Length:**

2.500 inches

#### **Body Diameter:**

1.062 inches

#### **Body Length:**

3.750 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Plain foil

#### **Electrical Polarization:**

Polarized

# **Capacitance Value Per Section:**

160.000 microfarads single section

## Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

5.0 milliamperes

### Nonderated Continuous Voltage Rating And Type Per Section:

350.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Aluminum

#### **Dissipation Factor At Reference Tempurature In Percent:**

18.0000

# Dc Leakage At Reference Temp:

1.000 milliamperes

# **Terminal Surface Treatment:**

Solder

## **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0