NSN 5910-00-420-2345

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-420-2345 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** Between 1.500 inches and 1.750 inches **Body Length:** 0.335 inches **Body Width:** 0.219 inches **Body Height:** 0.095 inches Center To Center Distance Between Terminals Parallel To Length: 0.125 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 22.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.0000 Dc Leakage At Reference Temp: 1.200 microamperes **Terminal Surface Treatment:**

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-420-2345

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0