NSN 5910-00-420-3259

Mica Dielectric Fixed Capacitor - Page 1 of 1



/iew Online at https://aerobasegroup.com/nsn/5910-00-420-3259

| View Online at https://aerobasegroup.com/nsn/5910-00-420-3259 |
|--|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.120 inches |
| Body Length: |
| 0.800 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.800 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 75.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 5100.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 500.0 dc single section |
| Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: |
| +0.0 to 70.0 single section |
| Tolerance Range Per Section: |
| -1.00 to 1.00 percent single section |
| Case Material: |
| Plastic |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 81349-mil-c-5+4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

A010b0

No **Fiig:**