## NSN 5910-00-422-3422

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-422-3422

**Body Style:** 

Piston

**Overall Length:** 

Between 0.720 inches and 0.780 inches

**Terminal Length:** 

1.000 inches

**Body Length:** 

Between 0.590 inches and 0.650 inches

**Overall Diameter:** 

Between 0.305 inches and 0.315 inches

**Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** 

-50.0/+50.0 single section

**Center To Center Distance Between Terminals Parallel To Length:** 

0.230 inches

**Terminal Diameter:** 

Between 0.032 inches and 0.040 inches

**Quality Factor At 25 Deg Celsius:** 

1000.0

**Fragility Factor:** 

Moderately rugged

**Inclosure Type:** 

Encased

**Adjustment Device Torque:** 

Between 1.000 inch-ounces and 8.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

**Mounting Facility Type And Quantity:** 

1 terminal

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Capacitance Range In Picofarads:** 

+1.0/+8.5 single section

**Nonderated Voltage Rating And Type:** 

750.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:** 

1 slotted screw

Material:

Glass capacitive electrode

**Terminal Type And Quantity:** 

1 solder stud and 2 wire lead

Shelf Life:

N/a

## NSN 5910-00-422-3422

Glass Dielectric Variable Capacitor - Page 2 of 2



| ı | 1 | n | iŧ | <b>1</b> | : N/ | lea |     |    | _ |   |
|---|---|---|----|----------|------|-----|-----|----|---|---|
| ı | u | n | IT | OI       | ١V   | ıea | เรเ | JI | е | : |

--

Demilitarization:

No

Fiig:

A096a0