NSN 5910-00-426-0330

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-426-0330 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.230 inches **Body Width:** 0.310 inches **Body Height:** 0.130 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.175 inches and 0.225 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 15.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 45.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.0000

Dc Leakage At Reference Temp: 3.000 microamperes **Terminal Surface Treatment:** Solder

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-426-0330

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf I	Life	е:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0