

View Online at <https://aerobasegroup.com/nsn/5910-00-426-9610>

**Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

1.250 inches

**Body Diameter:**

0.730 inches

**Body Length:**

0.167 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.313 inches and 0.437 inches

**Terminal Diameter:**

0.032 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Capacitance Value Per Section:**

1500.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-66.0/+22.0 with rated voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

1600.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

200000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

1.5000

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-11015/21d government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0