

View Online at https://aerobasegroup.com/nsn/5910-00-428-3418

# **Body Style:**

W/o mtg facilities, radial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

## **Body Diameter:**

0.350 inches

#### **Body Length:**

0.120 inches

### Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.190 inches and 0.310 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

# Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

# **Capacitance Value Per Section:**

47.000 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-470.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

# Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

### **Case Material:**

Plastic

### **Insulation Resistance At Reference Temp:**

50000.0 megohms

### **Quality Factor At Reference Temp:**

350.0000

### **Terminal Surface Treatment:**

Solder

# **Test Data Document:**

81349-mil-c-20+17 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0