## NSN 5910-00-430-2605

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-430-2605 **Body Style:** Rotary **Terminal Length:** 0.118 inches **Body Diameter:** Between 0.390 inches and 0.430 inches **Body Height:** 0.354 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -200.0 to 200.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.315 inches **Quality Factor At 25 Deg Celsius:** 300.0 **Fragility Factor:** Moderately rugged **Err Default:** 0.070 inches **Terminal Thickness:** 0.016 inches **Inclosure Type:** Encased **Adjustment Device Torque:** Between 0.560 inch-ounces and 5.600 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000.0 kilohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +2.0 to 8.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Material: Steatite base

2 printed circuit

**Terminal Type And Quantity:** 

## NSN 5910-00-430-2605

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Shelf	Life:
-------	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A096a0