

NSN 5910-00-430-2608 Ceramic Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-430-2608 **Body Style:** Rotary **Terminal Length:** 0.118 inches **Body Diameter:** Between 0.390 inches and 0.430 inches **Body Height:** 0.354 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -450.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -200.0 to 200.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.315 inches **Quality Factor At 25 Deg Celsius:** 500.0 **Fragility Factor:** Moderately rugged **Err Default:** 0.070 inches **Terminal Thickness:** 0.016 inches **Inclosure Type:** Encased **Adjustment Device Torque:** Between 0.560 inch-ounces and 5.600 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000.0 kilohms **Mounting Facility Type And Quantity:** 

2 terminal

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+2.5 to 23.0 single section

**Nonderated Voltage Rating And Type:** 

250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:** 

1 slotted screw

Material:

Steatite base

**Terminal Type And Quantity:** 

2 printed circuit

## NSN 5910-00-430-2608

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Shelf	Life:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A096a0