

View Online at https://aerobasegroup.com/nsn/5910-00-430-2608

De du Studer
Body Style:
Rotary
Terminal Length:
0.118 inches
Body Diameter:
Between 0.390 inches and 0.430 inches
Body Height:
0.354 inches
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:
-450.0 single section
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:
-200.0 to 200.0 single section
Center To Center Distance Between Terminals Parallel To Diameter:
0.315 inches
Quality Factor At 25 Deg Celsius:
500.0
Fragility Factor:
Moderately rugged
Err Default:
0.070 inches
Terminal Thickness:
0.016 inches
Inclosure Type:
Encased
Adjustment Device Torque:
Between 0.560 inch-ounces and 5.600 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
1000.0 kilohms
Mounting Facility Type And Quantity:
2 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Capacitance Range In Picofarads:
+2.5 to 23.0 single section
Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Material:
Steatite base
Terminal Type And Quantity:
2 printed circuit

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0