

View Online at <https://aerobasegroup.com/nsn/5910-00-430-5820>

**Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

1.500 inches

**Body Diameter:**

0.500 inches

**Body Length:**

0.125 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.375 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Forrestal class cv; safeguard class ars; virginia class cgn (41); oliver perry class ffg; spruance class dd (963); austin ship class lpd-4 amphibious transport docks; whidbey island class lsd; supply class aoe; tarawa class lha; nimitz class cvn

**Capacitance Value Per Section:**

0.025 microfarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-82.0/+22.0 without voltage applied single section

**Nonderated Operating Temp:**

Between 10.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

100.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-20.00/+80.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

7500.0 megohms

**Power Factor At Reference Temperature In Percent:**

3.0000

**Terminal Surface Treatment:**

Solder

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0