

View Online at <https://aerobasegroup.com/nsn/5910-00-430-5820>

Body Style:

W/o mtg facilities, radial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.500 inches

Body Length:

0.125 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.375 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Forrestal class cv; safeguard class ars; virginia class cgn (41); oliver perry class ffg; spruance class dd (963); austin ship class lpd-4 amphibious transport docks; whidbey island class lsd; supply class aoe; tarawa class lha; nimitz class cvn

Capacitance Value Per Section:

0.025 microfarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-82.0/+22.0 without voltage applied single section

Nonderated Operating Temp:

Between 10.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+80.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

7500.0 megohms

Power Factor At Reference Temperature In Percent:

3.0000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0