NSN 5910-00-432-0581

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-432-0581 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.688 inches **Body Width:** 0.515 inches **Body Height:** 0.343 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.721 inches and 0.844 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 3000.0 megohms **Capacitance Value Per Section:** 0.470 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 30000.0 megohms

Dissipation Factor At Reference Tempurature In Percent: 1.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:**

NSN 5910-00-432-0581

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| _ | | •• | • - | | | | |
|---|----|----|-----|-----|-------------|-----|----|
| 1 | em | | ゖっ | riz | 2 †1 | n | |
| _ | | ш | ıιa | 114 | au | VII | ١. |

No

Fiig:

A010b0