## NSN 5910-00-432-9144

**Body Style:** 

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-432-9144

W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Body Diameter:
1.499 inches
Body Length:
2.562 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
1835.0
Electrical Polarization:
Polarized
Section Quantity:
3
Capacitance Value Per Section:
12.000 microfarads all sections
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
450.0 dc all sections
Tolerance Range Per Section:
-10.00/+50.00 percent all sections
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
17.0000
Dc Leakage At Reference Temp:
110.000 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

4 tab, solder lug

## NSN 5910-00-432-9144

Electrolytic Fixed Capacitor - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-c-62/5 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0