

View Online at <https://aerobasegroup.com/nsn/5910-00-434-1734>

Thread Class:

2a

Body Style:

Piston

Overall Length:

0.480 inches

Bushing Diameter:

0.210 inches

Bushing Length:

Between 0.215 inches and 0.235 inches

Body Length:

0.270 inches

Overall Diameter:

Between 0.215 inches and 0.235 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-15.0/+15.0 single section

Quality Factor At 25 Deg Celsius:

10000.0

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encased

Terminal Location:

Circumference on end opposite adjustment control perpendicular

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Rotation:

8.0 turns counterclockwise

Adjustment Device Torque:

Between 0.400 inch-ounces and 4.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

64

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.190 inches

Capacitance Range In Picofarads:

+0.6/+6.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Thread Tolerance Class:

2a external

Terminal Type And Quantity:

1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0